

AUZ 01 INV - stainless steel wall-mounted toilet for handicapped people



AUZ 01 INV is a stainless steel wall-hung closet without automatics intended for handicapped people. The closet is based on standard AUZ 01, which is elevated and protracted to comply with the ordinance for products for disabled people. The pan is equipped by a plastic toilette seat from hardened plastic for higher comfort. A set with an AUZ 3 automatic flushing system and KZ 1 cantilever, or with an AUZ 5 (in-wall toilet module) flushing system can be completed. The AUZ 3 and AUZ 5 flushing systems and KZ1 cantilever need to be ordered separately. Automatic flushing systems use photocell sensor for contactless control. After leaving the scanning zone the flushing system is activated. The AUZ 01 INV assembly inlets are the same as for any commonly used ceramic closet. The stainless steel casing is made of 1.5 mm thick st. steel metal sheet. Because of its high resistance to damage, the AUZ 01 is intended mainly for social facilities with expected higher loads, such as highway lay-bays, public houses etc. where easy hygiene maintenance is required ? with use of the AUZ 3 flushing system for maximum water savings. AUZ 01 INV is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUZ 01 INV is a stainless steel wall-hung closet without automatics intended for handicapped people. The closet is based on standard AUZ 01, which is elevated and protracted to comply with the ordinance for products for disabled people. The pan is equipped by a plastic toilette seat from hardened plastic for higher comfort. A set with an AUZ 3 automatic flushing system and KZ 1 cantilever, or with an AUZ 5 (in-wall toilet module) flushing system can be completed. The AUZ 3 and AUZ 5 flushing systems and KZ1 cantilever need to be ordered separately. Automatic flushing systems use photocell sensor for contactless control. After leaving the scanning zone the flushing system is activated. The AUZ 01 INV assembly inlets are the same as for any commonly used ceramic closet. The stainless steel casing is made of 1.5 mm thick st. steel metal sheet. Because of its high resistance to damage, the AUZ 01 is intended mainly for social facilities with expected higher loads, such as highway lay-bays, public houses etc. where easy hygiene maintenance is required ? with use of the AUZ 3 flushing system for maximum water savings. AUZ 01 INV is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Requirements for setting up the construction

1. Set-up outlet d = 110 mm with the rubber sleeve for the pipe d = 90 mm
2. Water installation set up as per picture d = 34 - 50 mm according to chosen sealing
3. Set-up the cantilever or other system for hanging the closet
4. Set-up cable for power supply ? 12 V, 50 Hz from source of power supply ZAC (only for AUZ 3)
5. Set-up alcove for installation casket (only for AUZ 3)

Download information about the product

- [AUZ 01 INV data for projectants - \(.35 kB.\)](#)

Basic technical information
Water inlet
Minimum water flow capacity

d = 34 - 50 mm
70 l/min

Outlet	d = 90 mm
Required spacing between bolts	180 mm
Weight	22 kg

Figures

