

AUZ 02 - stainless steel free-standing toilet



AUZ 02 is a stainless steel toilet without automatics and is intended for free-standing. It is convenient in all places where it is not possible to use wall-hung toilet (e.g. in case of low carrying capacity of the wall). In standard version the outlet is directed into the floor. Outlet directed into the wall is possible on customer's wish. The sitting part is equipped with plastic sitting board. The housing of the toilet is made from the stainless steel of 1,5 mm thickness, the sitting part of 2 mm thickness. A set with an AUZ 3 automatic flushing system and KZ 1 cantilever can be completed. AUZ 02 is produced also in vandal-proof version (BSNZ 02) which is intended particularly for modernization of the prisons, diagnostic establishments and other institutions where security is paramount. Vandal-proof version does not include sitting board, all the edges are grinded down. AUZ 02 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUZ 02 is a stainless steel toilet without automatics and is intended for free-standing. It is convenient in all places where it is not possible to use wall-hung toilet (e.g. in case of low carrying capacity of the wall). In standard version the outlet is directed into the floor. Outlet directed into the wall is possible on customer's wish. The sitting part is equipped with plastic sitting board. The housing of the toilet is made from the stainless steel of 1,5 mm thickness, the sitting part of 2 mm thickness. A set with an AUZ 3 automatic flushing system and KZ 1 cantilever can be completed. AUZ 02 is produced also in vandal-proof version (BSNZ 02) which is intended particularly for modernization of the prisons, diagnostic establishments and other institutions where security is paramount. Vandal-proof version does not include sitting board, all the edges are grinded down. AUZ 02 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Complete delivery

1. stainless steel toilet including plastic seat
2. anchoring material

Requirements for setting up the construction


1. Water installation set up as per picture
2. Set-up alcove for installation casket (only for AUZ 3)
3. Set-up cable for power supply ? 12 V, 50 Hz from source of power supply ZAC (only for AUZ 3)
4. Set-up outlet d = 90 mm as per picture
5. Set-up the cantilever or other system for hanging the toilet

Download information about the product

- [AUZ 02 data for projectants - \(35 kB \)](#)

Basic technical information	Water inlet	d = 34 - 50 mm
	Min. water flow	70 ltrs./min
	Outlet	d = 90 mm
	Weight	19 kg

Figures



Reviews

There are yet no reviews for this product.