

AUZ 06N - stainless steel toilet including flushing cistern, for free standing



AUZ 06N is a free-standing toilet including stainless steel flushing cistern. The outlet can be directed into the wall or floor, provided suitable elbow pipe is used. The toilet is standardly equipped with grey seat made of hardened plastic (white or black seat or no seat are possible on order). Its design is based on AUZ 06 toilet and is convenient in all places where there is not sufficient carrying capacity of the wall and at the same time pressure flushing system cannot be used. The housing of the toilet is made from the stainless steel of 1,5 mm thickness, the sitting part of 2 mm thickness. AUZ 06N is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recomnend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet
[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUZ 06N is a free-standing toilet including stainless steel flushing cistern. The outlet can be directed into the wall or floor, provided suitable elbow pipe is used. The toilet is standardly equipped with grey seat made of hardened plastic (white or black seat or no seat are possible on order). Its design is based on AUZ 06 toilet and is convenient in all places where there is not sufficient carrying capacity of the wall and at the same time pressure flushing system cannot be used. The housing of the toilet is made from the stainless steel of 1,5 mm thickness, the sitting part of 2 mm thickness. AUZ 06N is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recomnend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1). Complete delivery

- 1. Stainless steel toilet
- 2. Plastic seat
- 3. Flushing cister including flushing mechanism

Requirements for setting up the construction

- 1. Set-up water inlet G 1/2"
- 2. Set-up water outlet into the wall or floor d = 110 mm with rubber sleeve for pipe d = 90 mm

Basic technical information	Water inlet	G 1/2"
	Material	AISI 304 (1,4301)
	Weight	30 kg
	Outlet	d = 90 mm

Figures

