

AUZ 3 - sensor-controlled WC flushing system



AUZ 3 is a sensor-controlled flushing system for lavatories. After leaving the scanning zone, the electromagnetic valve is opened and the flushing system is activated. The photocell sensor does not react to people passing by, and is not sensitive to daylight and artificial lighting. A manual press button is available when cleaning. An anchoring distance frame is used to level off any imprecision in setting the casket. The AUZ 3 automatic flushing system for lavatories is intended for social facilities, where a high standard of hygiene at maximum water savings is required, and it can be used for all types of closets. The most suitable type is a wall-hang closet, set-up on a KZ 1 mounting cantilever. This solution stands out because of its high aesthetic level and allows the toilet to be cleaned. The KZ 1 cantilever needs to be ordered separately.

Rating: Not Rated Yet
[Ask a question about this product](#)

Manufacturer: [AZP Bmo](#)

Description AUZ 3 is a sensor-controlled flushing system for lavatories. After leaving the scanning zone, the electromagnetic valve is opened and the flushing system is activated. The photocell sensor does not react to people passing by, and is not sensitive to daylight and artificial lighting. A manual press button is available when cleaning. An anchoring distance frame is used to level off any imprecision in setting the casket. The AUZ 3 automatic flushing system for lavatories is intended for social facilities, where a high standard of hygiene at maximum water savings is required, and it can be used for all types of closets. The most suitable type is a wall-hang closet, set-up on a KZ 1 mounting cantilever. This solution stands out because of its high aesthetic level and allows the toilet to be cleaned. The KZ 1 cantilever needs to be ordered separately.
Complete delivery

- 1. Installation casket
- 2. inlet bolting
- 3. outlet pipe
- 4. stainless steel casing with electronics cabinet
- 5. electromagnetic valve
- 6. anchoring distance frame
- 7. covering metal assembly plate
- 8. small assembly materials

Requirements for setting up the construction

- 1. Set-up water supply with a minimum water flow of 70 l/min as per picture (with a filter)
- 2. Set-up alcove 150x150x100 mm for installation casket
- 3. Set-up cable for power supply ? 12 V, 50 Hz from source of power supply ZAC
- 4. Set-up water supply to toilet bowl - pipe d = 34 mm

Basic technical information	Radius of sensor	self-adjusting
	Water inlet	G 3/4?
	Water pressure	0,1 ? 1,0 MPa

Adjustable time of flushing	0 ? 20 sec. (adjusted to 5 sec.)
Power supply	12 V, 50 Hz
Power requirement	6 VA
Source of power supply	ZAC 1/20 (max. 3 x AUZ 3)
	ZAC 1/50 (max. 8 x AUZ 3)
Weight	1,7 kg

Figures

