

## AFO 01.SCL - drinking fountain with cooling and spout for filling bottles designed to stand and to be attached to wall



AFO 01.SCL is a drinking fountain with cooling and spout for filling bottles designed to stand and to be attached to wall. User can select between uncooled water and water running through a flow cooler. Uncooled water is used for bottle filling as a standard ? can be changed. Start/stop control by piezo-buttons ? resistant solution. Facility keeper can set a time period after which the water flow automatically stops. The product contains a flow cooler. It is not a design with cooled tank only where ? after the pre-cooled amount of water is pumped out ? the user has to wait for the next charge to be cooled. Water supply is provided by a flexible hose, trap comprises an elastic flexible couple. Flexible design of water supply and outflow allows variable and easy connection of the drinking fountain as well as its dismantling. The drinking fountain is also manufactured in the following modifications: AFO 01 - wall mounted drinking fountain AFO 01.S - drinking fountain designed to stand and to be attached to the wall AFO 01.SL - drinking fountain with spout for filling bottles AFO 01.SC - drinking fountain with cooling Automatic drinking fountain (with a sensor) can be supplied per order. AFO 01.SCL is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AFO 01.SCL is a drinking fountain with cooling and spout for filling bottles designed to stand and to be attached to wall. User can select between uncooled water and water running through a flow cooler. Uncooled water is used for bottle filling as a standard ? can be changed. Start/stop control by piezo-buttons ? resistant solution. Facility keeper can set a time period after which the water flow automatically stops. The product contains a flow cooler. It is not a design with cooled tank only where ? after the pre-cooled amount of water is pumped out ? the user has to wait for the next charge to be cooled. Water supply is provided by a flexible hose, trap comprises an elastic flexible couple. Flexible design of water supply and outflow allows variable and easy connection of the drinking fountain as well as its dismantling. The drinking fountain is also manufactured in the following modifications: AFO 01 - wall mounted drinking fountain AFO 01.S - drinking fountain designed to stand and to be attached to the wall AFO 01.SL - drinking fountain with spout for filling bottles AFO 01.SC - drinking fountain with cooling Automatic drinking fountain (with a sensor) can be supplied per order. AFO 01.SCL is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Complete delivery

1. Stainless housing with cone
2. Electronics and control piezo-buttons
3. Water supply and electromagnetic valves
4. Flow cooler
5. Flexible hose outflow
6. Fixing and connecting material

Requirements for setting up the construction

1. Set up water outlet  $d = 40 \text{ mm}$
2. Set up water inlet G 1/2"
3. Electric socket 230 V, or set up electric cable CYKY 3C x 1,5

## Basic technical information dimensions

water outlet  
water inlet  
water pressure  
power supply  
power input  
weight

330 x 900 x 365 mm  
 $d = 40 \text{ mm}$   
G 1/2"  
0,2 ? 0,6 MPa, recommended 0,3 MPa  
230 V, 50 Hz  
830 W  
25 kg

## Figures

