

AUM 011 - stainless steel sensor-controlled washbasin



AUM 011 is the stainless steel, sensor-controlled, wall-mounted washbasin. The basin is equipped with a stainless steel facing, aerator and sensor. Water turns on automatically when the user's hands are placed within the sensor's range and turns off when they have been removed. Water stops running with a certain time delay after the hands have been removed from the scanning zone. The washbasin is equipped with the mechanism against excess pressure of hot and cold water. AUM 011 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUM 011 is the stainless steel, sensor-controlled, wall-mounted washbasin. The basin is equipped with a stainless steel facing, aerator and sensor. Water turns on automatically when the user's hands are placed within the sensor's range and turns off when they have been removed. Water stops running with a certain time delay after the hands have been removed from the scanning zone. The washbasin is equipped with the mechanism against excess pressure of hot and cold water. AUM 011 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Complete delivery

1. Sink with sheathing
2. Aerator
3. Electronics with the sensor
4. Electromagnetic valve
5. Corner valve with filter (AUM 011.2, .TV ? 2 pcs)
6. Spherical valve (AUM 011.2 TV)
7. Mixing valve (AUM 011.2)
8. Thermostatic valve (AUM 011.TV)
9. Through flow water heater (AUM 011.E)
10. Source of power supply ZAC E ? 12 V, 50 Hz (AUM 011.E)
11. Waste siphon
12. Connecting hoses
13. Cantilever
14. Fittings

Requirements for setting up the construction

1. The water supply set up ? see the picture
2. The outlet set up on D= 40 mm
3. The power-supply cable is fixed for powering 12 V, 50 Hz from power-supply source ZAC (not applicable for AUM 011.E)
4. The power-supply cable CYKY 32C x 1,5 ? 2,5 for AUM 011.E is wired

Download information about the product

- [AUM 011.1 data for projectants - \(98 kB \)](#)
- [AUM 011.1B data for projectants - \(98 kB \)](#)
- [AUM 011.2 data for projectants - \(98 kB \)](#)
- [AUM 011.2B data for projectants - \(98 kB \)](#)
- [AUM 011.E data for projectants - \(98 kB \)](#)
- [AUM 011.TV data for projectants - \(98 kB \)](#)
- [AUM 011.TVB data for projectants - \(98 kB \)](#)

Basic technical information	Sensor radius	self-adjusting
	Water inlet	G1/2"
	Outlet	D=40 mm
	Inner basin dimension	370 x 240 x 150 mm
	Adjustable after-action delay time	0 ? 4 s (set on 1 sec)
	AUM 011.1, .2, .TV	
	Water pressure	0,2 ? 0,6 MPa
	Electric powering	12V, 50 Hz, or for battery versions 6V (4 x AA battery)
	Input	3 500 W
	Powering source	ZAC 1/20 (max. 3 x AUM 011)
	Electricity protection	IP 54
	Weight	12,5 kg
	AUM 011.E	
	Recommended pressure	0,3 MPa (without variances and air bubbles)
	Power supply	230 V, 50 Hz

Figures

