

## AUM 013N.TV - washbasin without casing with thermostatic valve - 12V, 50 Hz



AUM 013 is a new stainless wash basin designed for normal conditions. Thanks to its attractive design it can be used at any place where ceramic wash basins would normally be used. The wash basin is produced in two standard models: wash basin without cover (AUM 013N) and more rigid model with cover (AUM 013Z). Surface finish is made by balottini sand-blasting resulting in velvet mat design. The wash basin is either delivered separately as the bowl with a hole (33 mm diameter) for pillar mixer or as a set equipped by popular AUM 3 automatic sensor mixer in all designs - for pre-mixed (one) water, for two waters or with thermostatic valve. All models are produced to be supplied from 12 V, 50 Hz source (ZAC source) or from 6 V batteries (4 AA batteries) AUM 013 washbasin (all version types) is manufactured from the stainless steel AISI 304. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUM 013 is a new stainless wash basin designed for normal conditions. Thanks to its attractive design it can be used at any place where ceramic wash basins would normally be used. The wash basin is produced in two standard models: wash basin without cover (AUM 013N) and more rigid model with cover (AUM 013Z). Surface finish is made by balottini sand-blasting resulting in velvet mat design. The wash basin is either delivered separately as the bowl with a hole (33 mm diameter) for pillar mixer or as a set equipped by popular AUM 3 automatic sensor mixer in all designs - for pre-mixed (one) water, for two waters or with thermostatic valve. All models are produced to be supplied from 12 V, 50 Hz source (ZAC source) or from 6 V batteries (4 AA batteries) AUM 013 washbasin (all version types) is manufactured from the stainless steel AISI 304. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1). Complete delivery

1. sink with or without sheathing
2. automatic tap with electronics (not for version type without tap)
3. elmag. valve (not for version without tap, 2x for version with hot and cold water)
4. corner valve with filter (not for version without tap, 2x for version with hot and cold water and thermostat)
5. spherical valve (not for version with thermostat)
6. thermostatic valve (only for version with TV)
7. outlet siphon
8. connecting hoses (not for version without tap)
9. small assembly fittings
10. AA battery 1,5V - 4pcs.

Requirements for setting up the construction

1. Set-up outlet  $d = 40$  mm
2. Set-up water inlet as per picture (only for version type including automatic tap)
3. Set-up cable for power supply ? 12 V, 50 Hz from source of power supply ZAC ? only for 12 V version type

Download information about the product


- [AUM 013 data for projectants - \( 45 kB \)](#)



- [AUM 013N data for projectants - \( 45 kB \)](#)
- [AUM 013N.1 data for projectants - \( 45 kB \)](#)
- [AUM 013N.1B data for projectants - \( 45 kB \)](#)
- [AUM 013N.2 data for projectants - \( 45 kB \)](#)
- [AUM 013N.2B data for projectants - \( 45 kB \)](#)
- [AUM 013N.TV data for projectants - \( 45 kB \)](#)
- [AUM 013N.TVB data for projectants - \( 45 kB \)](#)
- [AUM 013Z data for projectants - \( 45 kB \)](#)
- [AUM 013Z.1 data for projectants - \( 45 kB \)](#)
- [AUM 013Z.1B data for projectants - \( 45 kB \)](#)
- [AUM 013Z.2 data for projectants - \( 45 kB \)](#)
- [AUM 013Z.2B data for projectants - \( 45 kB \)](#)
- [AUM 013Z.TV data for projectants - \( 45 kB \)](#)
- [AUM 013Z.TVB data for projectants - \( 45 kB \)](#)

Basic technical information	Radius of sensor	self-adjusting
	Water inlet	G 1/2"
	Water outlet	d = 40 mm
	Inner dimensions of sink	480 x 300 x 145 mm
	Adjustable time of after-flow delay	0-4 s (adjusted to 1 s)
	Water pressure	0,1-1,0 Mpa (12 V version)0,2-0,8 Mpa (battery version)
	Power supply	12V, 50 HZ, for battery version 6V DC (4 x AA battery)
	Power requirement	6VA, 10VA version for hot and cold water
	Source of power supply	ZAC 1/20 (max. 3x version with one water or thermostatic valve; max. 2x version for hot and cold water)
		ZAC 1/20 (max. 8x version with one water or thermostatic valve; max. 5x version for hot and cold water)
	IP protection	IP 55
	Weight	5-10 kg according to version type

Figures



Reviews

There are yet no reviews for this product.