

SA 2 - surface shower unit



SA 2 is a surface shower unit intended for replacement of ordinary taps during reconstructions of social facilities. The SA 2 shower unit is wall-mounted without the necessity of additional construction work. It is designed to be assembled onto existing water inlets. The unit is equipped with an electromagnetic valve which opens the water inlet. The user operates the shower by means of a press button. SA 2 shower units are intended for usage in connection with AZP Brno coin-operated controls (version types MAS 1, MAS 2). SA 2 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description SA 2 is a surface shower unit intended for replacement of ordinary taps during reconstructions of social facilities. The SA 2 shower unit is wall-mounted without the necessity of additional construction work. It is designed to be assembled onto existing water inlets. The unit is equipped with an electromagnetic valve which opens the water inlet. The user operates the shower by means of a press button. SA 2 shower units are intended for usage in connection with AZP Brno coin-operated controls (version types MAS 1, MAS 2). SA 2 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Complete delivery

1. stainless steel casing
2. control button
3. shower arm SP 4
4. electromagnetic valve
5. thermostatic valve (SA 2.TV)
6. corner valve (SA 2.TV)
7. connecting hoses
8. bearing beam
9. small assembly materials

Requirements for setting up the construction

1. Set up water inlet
2. Set up cable for power supply to be connected with MAS
3. Assembly of the SA 2 subsurface unit does not need any particular construction setting. Construction of the armature enables connection to existing hot and cold water inlet with spacing from 90 to 160 mm, at the height of 950 ? 1 150 mm.

Basic technical information

Water inlet
Water pressure
Power supply

G 1/2?
0,1 ? 1,0 MPa
12 V, 50 Hz

Power requirement
Source of power supply
Weight

5 VA
MAS 1 or MAS 2
12 kg

Figures

