

COS 1 - clock controlled flushing system



COS 1 is a clock controlled flushing system for one urinal, group of urinals or a urinal trough. It is possible to set up periodical flushing during a day, interval between the flushes or duration of flushing. COS 01 flushing system can also use as an actuating signal an external source, for example bell during a recess at school. Flushing system can be also installed outside of the bathroom, which prevents it from unauthorized handling or a voluntary waste.

Rating: Not Rated Yet  
[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description COS 1 is a clock controlled flushing system for one urinal, group of urinals or a urinal trough. It is possible to set up periodical flushing during a day, interval between the flushes or duration of flushing. COS 01 flushing system can also use as an actuating signal an external source, for example bell during a recess at school. Flushing system can be also installed outside of the bathroom, which prevents it from unauthorized handling or a voluntary waste.  
Requirements for setting up the construction

- 1. Set up the an alcove in the wall
- 2. Set up a cable for power supply 230 V, 50 Hz
- 3. Set up a cable for the flushing valve connection
- 4. Set up an external control input (for version with an external control)

Basic technical information	Input voltage	230 V, 50 Hz
	Power requirement	6 VA
	Output voltage	12 V, 50 Hz
	Dimensions of the box	280 x 225 x 100 mm

Figures

