

SPS 01.3 Kültéri zuhanyoszlopok (4 használó számára)



SPS 01 is an integral stainless steel shower column intended for outdoor and indoor swimming pools, summer camps etc. The shower is operated by a press valve. There are two ways of anchoring the column, grapppling by concreting or anchoring by means of screws and joggles. The basic version of the SPS 01 is equipped by one shower head and a press valve for water release. The column can be set up with a photocell head for contactless control and thermostatic valves to order. SPS 01 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Értékelés: Még nincs értékelés

[Tegye fel kérdését a termék?](#)

Gyártó: [AZP Brno](#)

Leírás

SPS 01 is an integral stainless steel shower column intended for outdoor and indoor swimming pools, summer camps etc. The shower is operated by a press valve. There are two ways of anchoring the column, grapppling by concreting or anchoring by means of screws and joggles. The basic version of the SPS 01 is equipped by one shower head and a press valve for water release. The column can be set up with a photocell head for contactless control and thermostatic valves to order. SPS 01 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Szállított termékek

1. integral stainless steel shower column
2. pressure valve
3. shower arm
4. anchoring construction
5. press valve 1, 2, 4
6. shower arm 1, 2, 4
7. connecting material

További információk a termék?

- [SPS 01-1 data for projectants - \(79 kB \)](#)
- [SPS 01-2 data for projectants - \(92 kB \)](#)

- [SPS 01-3 data for projectants - \(79 kB \)](#)

Alapvető műszaki adatok Víz becsatlakozás

Víz nyomás

Water flow (one shower arm)

Height

Súly

G 1/2"


0,2 - 0,6 MPa

körülbelül 7,5 l/min.

2 m

50 kg

Ábrák



Vélemények

Még senki sem nyilvánított véleményt erről a termékről.